

R-26FA



TAKE YOUR MOVIES AND MUSIC TO NEW HEIGHTS

Our proprietary speaker technologies are ideal for delivering the most immersive, impactful 360° Dolby Atmos® listening experience. Controlled directivity and high-performance have been an integral part of Klipsch acoustic design principals for the better part of a century.

90x90 TRACTRIX HORN

Our exclusive Tractrix® Horn technology and aluminum tweeters deliver the most impressive high-end response and greater extension, enhanced imaging and powerful dynamics. This creates the cleanest, most natural sound possible.

LINEAR TRAVEL SUSPENSION (LTS) TWEETER

A Linear Travel Suspension minimizes distortion for enhanced, detailed performance. LTS Tweeters have been a hallmark of previous Reference lines, as well as our flagship Klipsch Palladium series, making it a core component of some of the best speakers in the world.

SPUN COPPER IMG WOOFERS

Injection Molded Graphite (IMG) woofers are exceptionally light while being extremely rigid-providing remarkable low frequency response, with minimal cone breakup and distortion. When paired with the Tractrix Horn-loaded LTS tweeter, it provides speaker efficiency highest in its class.

FRONT-FIRING PORT

Perfectly matched to the cabinet and woofers, the front placement design creates ideal airflow with minimal distortion.

MDF CABINET WITH BRUSHED POLYMER VENEER FINISH

Contemporary aesthetic with absolute durability that results in a seamless integration into any décor.

DUAL 5-WAY BINDING POSTS

Sturdy, versatile and high quality terminals that provide the benefits of bi-wiring and bi-amping.

STRONG, FLEXIBLE, REMOVABLE GRILLE

Adds a rich, refined look that is acoustically transparent.

SPECIFICATIONS - MAIN CHANNEL

FREQUENCY RESPONSE	38Hz - 24kHz +/- 3dB
SENSITIVITY	97dB @ 2.83V / 1m
POWER HANDLING (CONT/PEAK)	100W / 400W
NOMINAL IMPEDANCE	8 Ohms Compatible
CROSSOVER FREQUENCY	1800Hz
HIGH FREQUENCY DRIVER	1" (2.54cm) Aluminum diaphragm compression driver mated to 90° x 90° square Tractrix® Horn
LOW FREQUENCY DRIVER	Dual 6.5" (16.5cm) copper spun magnetically shielded IMG Woofers
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass-Reflex via front-firing port
INPUTS	Dual Binding Posts / Bi-wire / Bi-amp
HEIGHT	39" (99.1 cm)
WIDTH	7.8" (19.8 cm)
DEPTH	16.25" (41.3 cm)
WEIGHT	52 lbs (23.6 kg)
FINISH	Brushed Black Polymer Veneer
BUILT FROM	2017

SPECIFICATIONS - HEIGHT CHANNEL

FREQUENCY RESPONSE	Conforms to Dolby Atmos Specification
SENSITIVITY	Conforms to Dolby Atmos Specification
POWER HANDLING (CONT/PEAK)	75W / 150W
NOMINAL IMPEDANCE	8 Ohms Compatible
HIGH FREQUENCY DRIVER	1" Aluminum LTS Tweeter with Hybrid Tractrix Horn
LOW FREQUENCY DRIVER	5.25" Cerametallic Cone Woofer
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Acoustic Suspension
INPUTS	Single Binding Posts