



## **Technical Data Sheet**

## PRS4 - Passive - HDMI Cable



## Designed for high performance applications

Kordz PRS4 Passive HDMI Cables are designed to meet the high demands and rigour of professional integration. The Kordz PRS4 range features cables that are compact, tough and flexible with a 2Kg retention force die-cast connector. Kordz PRS<sup>4</sup> HDMI Passive Cables support the full features and benefits of the latest HDMI technology when using 4K HFR or 8K devices.

- · Ultra High Speed certified
- 48Gbps support for 8K/10K, HDR, VRR, HFR, 3D, FRL
- Robust engineering and construction with premium materials
- 15μ" gold-plated solid copper pins
- Compact connector with full internal zinc-alloy diecast housing
- Easy installation aided by the unique Kordz shark-nose dust-cap
- Convenient easy tear bulk packaging minimising waste on site
- UL CMG rating
- Installer friendly packaging
- High contrast detailed labelling with inventory management design
- Backed by the Kordz Lifetime Guarantee
















Technical Specifications		Reference Standards:		
HDMI Cable Certification		0.5m to 5.0m Lengths		
HDMI CTS (Certified Test Specific	cations)	Ultra High Speed HDMI® Cable		
Certified Data Rate		12.0Gbpsc, 48Gbps agg		
Supported Data Rate		≥12.0Gbpsc, 48Gbps agg (8K UHD)		
HDMI Clock		1200MHz		
Construction				
Primary Conductors		Solid 30-26 AWG OFC, length dependent		
Insulation	FRL/TMDS Pairs	Polyethylene		
	4C + HEAC Pairs	HDPE / Polyethylene		
Shielding	FRL/TMDS Pairs	AL/Mylar, 100% Coverage with 25% Overlapping		
	Overall	AL/Mylar, 125% Coverage + Tinned copper braid, min 85% coverage		
Cable Jacket Material		UL CMG fire-rated PVC composite materials		
HDMI Connector Shell		Anti-fatigue die cast Zn alloy, 1µ" 24K Gold plated		
HDMI Connector Pins		Solid OFC, 15µ" 24K Gold plated		
Termination		High frequency soldering		
HDMI Back-shell		ABS front shell with PVC injection moulded boot and strain relief		
Mechanical				
Cable Diameter	0.5m - 3.0m	30 AWG 6.0mm   0.24in Ø		
	4.0m - 5.0m	26 AWG 8.0mm   0.31in Ø		
Mounting Depth		Cable gauge dependent (see below)		
Cable Bend Radius	0.5m - 3.0m	30.0mm   1.18in		
	4.0m - 5.0m	40.0mm   1.57in		

Part No	Length	AWG	Technology	Inner Ctn Qty	Master Ctn Qty
K36426-0050-CH	0.5m   1' 8"	30	Passive	15	90
K36426-0100-CH	1.0m   3' 3"	30	Passive	12	72
K36426-0150-CH	1.5m   4' 11"	30	Passive	10	60
K36426-0200-CH	2.0m   6' 6"	30	Passive	8	48
K36426-0300-CH	3.0m   9' 10"	30	Passive	6	36
K36426-0400-CH	4.0m   13' 1"	26	Passive	8	24
K36426-0500-CH	5.0m   16' 4"	26	Passive	6	18



Kordz products are sold with a limited warranty as outlined at: www.kordz.com@2021 Kordz International. All rights reserved. Kordz Connectivity. Assured & Kordz range logos are trademarks or registered trademarks of Kordz International in Hong Kong and in other countries. All other trademarks are the property of their respective owners.