

E-Vision 6800 WUXGA 3D

6,500 ANSI Lumens | Contrast Ratio: 2,400:1 (Dynamic Black) 1,000:1 native | Part No:116-051

E-Vision 6800 Series Digital Projectors

DIGITAL  **PROJECTION****Colour System:**

4 Segment RGWB Colour Wheel for maximum brightness.
6 Segment RGBCMY Colour Wheel for optimised colourimetry - user swappable.

DMD Specification:

1920 x 1200 pixels native, +/- 12° tilt angle
Fast transit pixels for smooth greyscale and improved contrast.

Aspect Ratio:

16x10

Display Type:

1 x 0.67" DarkChip™ DMD™

Fill Factor

87%

Key Features

Video & Graphics Processing

- HDMI 1.4 for Side by Side, Frame Packing & Top Bottom 3D Formats.
- BrilliantColor™ for increased system brightness.
- DynamicBlack™ for improved black levels in dark scenes.
- Independent control of hue, saturation and gain for primary and secondary colours.
- The projector automatically detects interlaced video and implements 3:2 or 2:2 extraction as appropriate, with pixel based, motion adaptive interpolation and auto cadence correction.
- Image enhancement for MPEG, Mosquito noise & Colour Transients in composite sources.

Geometry Correction

- Vertical and horizontal keystone correction.

HDBaseT® Interface

- Built in support for transmission of uncompressed High Definition Video over standard CAT5e/6 LAN cable.
- Allows projector to be placed up to 100m from source with low cost cabling.

Source Compatibility:

HDMI including Deep Color™ processing and 3D standards.

Graphics standards up to 1920 x 1200 resolution at 60Hz via DVI, HDMI or VGA.

DVI single link with HDCP compliance.

Component Video (SD and HD) via YPrPb, RGB or RGBS.

S-Video (PAL, NTSC & SECAM)

Composite Video (PAL, NTSC & SECAM)

Inputs/Outputs

Video & Computer			Communication & Control		
Type	Connector	Qty	Type	Connector	Qty
HDMI 1.4	HDMI	1	LAN	RJ45	1
DVI-D - Single Link DVI	DVI	1	RS232	9-pin D Sub	1
HDBaseT	RJ45	1	12V Trigger	3.5mm Stereo Jack	1
VGA / Analog RGB In	15-pin D-Sub	1	Service Port	USB Type B	1
VGA / Analog RGB Out	15-pin D-Sub	1			
Component Video	3 x RCA	1			
Component Video	5 x BNC	1			
S-Video	4-pin Mini DIN	1			
Composite Video	RCA	1			
3D Formats Supported			HDTV Formats Supported		
Frame Packing			1080p (24Hz, 25Hz, 30Hz, 50Hz, 60Hz),1080i (50Hz, 60Hz), 720p (50, 60Hz)		
Side By Side (half)					
Top and Bottom					
Computer Compatibility			Bandwidth		
Up to 1920 x 1200			165 MHz on analog RGB 165 Megapixels per second on DVI		
Remote Control			Automation Control		
IR Remote Control			LAN RS232 Crestron RoomView® Connected PJLink		
On-Board keypad					
Colour Temperature					
User selectable from 6500 to 9300K					
Lamp Type			Typical Lamp Life		
2 x 280W High Intensity Discharge			Full Power: 2500 hours (up to 5000 hours in lamp sequential mode) Eco Mode : 3000 hours (up to 6000 hours in lamp sequential mode)		
Lenses					
Lens	Part No.	Focus Range	Lens Shift		
0.76 :1 fixed	112-499	0.81m - 5.08m	none		
0.75 - 0.93 :1 zoom	115-339	1.02m - 12.7m	Vert: 0.5 (U) 0 (D) frame, Hor: 0.1(L) 0.1 (R) frame		
1.25 - 1.79 :1 zoom	112-500	1.33m - 11.73m	Vert: 0.5 (U) 0 (D) frame, Hor: 0.1(L) 0.1 (R) frame		
1.72 - 2.27 :1 zoom	112-501	1.83m - 14.9m	Vert: 0.5 (U) 0 (D) frame, Hor: 0.1(L) 0.1 (R) frame		
2.22 - 3.67 :1 zoom	112-502	2.36m - 24.2m	Vert: 0.5 (U) 0 (D) frame, Hor: 0.1(L) 0.1 (R) frame		
3.58 - 5.38 :1 zoom	112-503	3.8m - 35.35m	Vert: 0.5 (U) 0 (D) frame, Hor: 0.1(L) 0.1 (R) frame		
5.31 - 8.26 :1 zoom	112-504	5.59m - 54.8m	Vert: 0.5 (U) 0 (D) frame, Hor: 0.1(L) 0.1 (R) frame		
Lens Mount					
Motorised shift, zoom and focus.					
Mechanical Mounting			Orientation		
Front/Rear Table			Table Top or Inverted: Yes		
Front/Rear Ceiling			Pointing Up: Yes		
Adjustable Front/Rear Feet			Pointing Down: Yes		
			Roll (Portrait): +/-10° from horizontal		
Power Requirements			Power Consumption		
100-240VAC 50/60Hz single phase			715W		
Thermal Dissipation			Fan Noise		
2440 BTU/Hour			39 dBA, Eco 34dBA		
Operating/Storage Temperature			Operating Humidity		
Operating: 5 to 40C (41 to 104F) Storage: -10 to 60C (14 to 140F)			5% to 90% non-condensing		
Weight (Chassis Only)			Dimensions		

16.1 kg
35.5 lb

L: 38.5cm W: 50.5cm H: 20.9cm
L: 15.2in W: 19.9in H: 8.2in

Safety & EMC Regulations

CE, CB, FCC Class A, UL, CCC

Accessories

Accessory	Part No.
Lamp & Housing	116-380
Infrared Remote (replacement)	112-377
Ceiling Mount Kit w/plate & 500mm pole	112-940
Gyrolock Ceiling Mount Kit w/plate & 230 - 300mm adjustable pole	112-410
Swivel Truss Mount Kit - fully adjustable for up to 50kg	116-201
Replacement Filter Set	116-377

**Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.*

Downloads

[PDF CAD Drawings](#)

[User Guides](#)

[AUTOCAD Drawings](#)

[Important Information](#)

Specifications subject to change without notice. Digital Projection version: - ©2012 Digital Projection.
DLP®, Digital Light Processing™ and DMD are trademarks of Texas Instruments, Inc

DIGITAL PROJECTION, LTD GREENSIDE WAY, MIDDLETON MANCHESTER, UK. M24 1XX
T: +44.161.947.3300 | F: +44.161.684.7674 | www.digitalprojection.co.uk

DIGITAL PROJECTION, INC 55 CHASTAIN ROAD, SUITE 115 KENNESAW, GA. 30144
T: 770.420.1350 | F: 770.420.1360 | www.digitalprojection.com

DIGITAL PROJECTION, CHINA TOWER C, RM C1202, CAI FU JIA YUAN, NO. 19 XIAO YING STREET, CHAOYANG DISTRICT BEIJING, PR CHINA 100101
T: +86.10.58239771 | F: +86 10 58239770

DIGITAL PROJECTION, ASIA 16 NEW INDUSTRIAL ROAD, #02-10 HUDSON TECHNOCENTRE SINGAPORE 536204
T: +65.6284.1138 | F: +65.6284.1238